

M210

New 750 cfm alternative to single axle M200

[CATERPILLAR engine with exhaust emission Tier 3]

For extreme conditions:
-10°C up to +50°C

Easy to operate:
SIGMA CONTROL SMART

Safe workplace:
parking brake

For a long working day:
420l Diesel



Compact design:
3 units in 40ft container

Options like M235:
air treatment or
refinery version

	<u>M200</u>	<u>M210</u>	<u>M235</u>
Engine	CAT	CAT	CUMMINS
Nominal power	146kW	146kW	201kW
m ³ /min @ 7 bar	21.2 (750 cfm)	21.2 (750 cfm)	-
8.6 bar	19.7 (700 cfm)	19.7 (700 cfm)	23.3 (825 cfm)
10 bar	18.0 (640 cfm)	18.0 (640 cfm)	22.6 (800 cfm)
12 bar	16.0 (565 cfm)	-	19.8 (700 cfm)
14 bar	14.5 (515 cfm)	-	18.1 (640 cfm)

750 cfm

special offer M200 & M210



Construction compressors MADE IN GERMANY
powered by CATERPILLAR engine with exhaust emission Tier 3

M200



M210



M200

Engine	CAT C6.6
Nominal power	146kW
m ³ /min @ 7 bar	21.2 (750 cfm)
8.6 bar	19.7 (700 cfm)
10 bar	18.0 (640 cfm)
12 bar	16.0 (565 cfm)
14 bar	14.5 (515 cfm)

M210

CAT C6.6
146kW
21.2 (750 cfm)
19.7 (700 cfm)
18.0 (640 cfm)
-
-

M200:

roadportable with single axle
incl. overrun and parking brake

M210:

4 wheels with steering axle
incl. parking brake
for safe workplace at construction site

both:

Designed for extreme conditions
ambient temperatures: -10°C up to 50°C (standard version)